

How to Use

BOAT Magic®

The User Friendly Hull and Outdrive Cleaner!™

Cleaning Toilets and General Cleaning



BOAT Magic is the best way to remove stubborn mineral deposits from porcelain and plastics. It can be used to remove calcium and other stain build-up on toilets and other non-porous, non-metal surfaces.

READ INSTRUCTIONS IN THEIR ENTIRETY BEFORE PROCEEDING.

FOR TOILET, PUMP, AND DISCHARGE HOSE SCALE REMOVAL:

DILUTION:

Dilute 1 part BOAT Magic to 10 parts water.

APPLICATION:

- Pour two cups of diluted 1:10 solution into the toilet.
- Use toilet brush to agitate and ensure solution contact.
- Once the fizzing completes, pump the toilet-intake enough to close and empty the bowl into the pump.
- Dwell 2-4 minutes in the pump to remove scale.
- Pump again to flush solution into the discharge hose.
- Dwell 2-4 minutes to remove the scale in the discharge hose.
- Repeat if necessary as required with heavy scaling.

To remove scale on the anti-siphon valve in the discharge line, soak in warm soapy water to dissolve the deposits.

FOR GENERAL CLEANING:

DILUTION:

Dilute 1 part BOAT Magic to 4 parts water.

APPLICATION:

- Prepare a baking soda solution prior to application. Baking soda solution can be obtained by dissolving 2 - 4 parts sodium bicarbonate (baking soda) to 100 parts water.
- Wearing gloves, apply with acid resistant spray bottle or sponge. Lightly scrub surface with soft bristle brush or scouring pad. Rinse thoroughly with water. If second application is needed, repeat and rinse.
- **Rinse again with water.**
- Apply baking soda solution to surface to neutralize any remaining acid. Scrub with scouring pad.
- Flush thoroughly with water.

BOAT Magic is not an algacide or molluscide and is not intended to repel or control the growth of algae or marine life.

PRECAUTIONS:

- While using BOAT Magic, protective eyewear and gloves are always required.
- **Active ventilation is required when working indoors.**
- **When diluting, ALWAYS add the BOAT Magic to water, NOT water to the BOAT Magic. This eliminates the potential of an unwanted reaction that may cause dangerous splashing to occur.**
- **Do not apply to dry surfaces.** Always wet surface prior to application, including any adjoining areas, in case of accidental spillage or overspray.
- **Do not allow the surface to dry with BOAT Magic solution on it.**
- Use caution when applying BOAT Magic to avoid contact with other surfaces, such as wood or metal, as an unwanted reaction and discoloration of surfaces could occur.

